

TECHNICAL DATA

SERIES	MODEL	WORKING POWER KN	BENDING LENGTH mm	DISTANCE BETWEEN UPRIGHTS mm	THROAT DEPTH mm	RAM STROKE mm	DISTANCE BETWEEN BAD-RAM mm	RAM SPEED			MAIN MOTOR POWER Kw	APPROXIMATE WEIGHT Kg
								DOWNSTROKE mm/sec	WORK mm/sec	UPSTROKE mm/sec		
SPS/N 100	SPS/N 100/31	1000	3100	2600	400	250	440	100	10	130	7,5	9000
	SPS/N 100/41		4100	3100						130		10100
	SPS/N 100/61		6100	5100						80		16800
SPS/N 130	SPS/N 130/31	1300	3100	2600	400	250	440	100	10	120	11	10600
	SPS/N 130/41		4100	3100						120		11900
	SPS/N 130/61		6100	5100								19900
SPS/N 160	SPS/N 160/31	1600	3100	2600	400	250	440	100	10	120	15	11900
	SPS/N 160/41		4100	3100						120		13400
	SPS/N 160/51		5100	4100								16800
	SPS/N 160/61		6100	5100								21900
SPS/N 200	SPS/N 200/31	2000	3100	2600	400	300	490	100	10	120	18,5	14200
	SPS/N 200/41		4100	3100						120		15900
	SPS/N 200/61		6100	5100						120		24300
	SPS/N 200/81		8100	7100						75		34400
SPS/N 250	SPS/N 250/31	2500	3100	2600	400	300	490	100	8	100	18,5	17100
	SPS/N 250/41		4100	3100						100		19200
	SPS/N 250/61		6100	5100						100		29000
	SPS/N 250/81		8100	7100						70		40800
SPS/N 300	SPS/N 300/31	3000	3100	2600	400	300	490	100	8	110	22	18400
	SPS/N 300/41		4100	3100						110		20600
	SPS/N 300/61		6100	5100						110		31200
	SPS/N 300/81		8100	7100						75		43600
SPS/N 400	SPS/N 400/41	4000	4100	3600	500	400	570	115	10	105	37	32000
	SPS/N 400/61		6100	5600								44000
	SPS/N 400/81		8100	7600								60000
SPS/N 500	SPS/N 500/41	5000	4100	3600	500	400	570	100	8	95	37	38000
	SPS/N 500/61		6100	5600								49000
	SPS/N 500/81		8100	7600								65000
SPS/N 600	SPS/N 600/63	6000	6300	5600	500	500	700	100	8	90	45	65000
	SPS/N 600/83		8300	7600								77000
SPS/N 800	SPS/N 800/63	8000	6300	5600	500	500	700	100	8	90	55	77000
	SPS/N 800/83		8300	7600								97000
SPS/N 1000	SPS/N 1000/66	10000	6600	5600	750	500	900	90	8	80	75	105000
	SPS/N 1000/86		8600	7600								125000
	SPS/N 1000/106		10600	9600								150000
SPS/N 1250	SPS/N 1250/66	12500	6600	5600	750	500	900	90	7	75	2 x 45	130000
	SPS/N 1250/86		8600	7600								145000
	SPS/N 1250/106		10600	9600								173000
SPS/N 1500	SPS/N 1500/66	15000	6600	5600	750	500	900	90	7	70	2 x 45	142000
	SPS/N 1500/86		8600	7600								171000
	SPS/N 1500/106		10600	9600								197000
SPS/N 2000	SPS/N 2000/88	20000	8800	7600	750	500	1000	90	6,5	65	2 x 75	200000
	SPS/N 2000/108		10800	9600								231000
SPS/N 2500	SPS/N 2500/88	25000	8800	7600	750	500	1000	90	6,5	65	2 x 75	234000
	SPS/N 2500/108		10800	9600								270000